

# Product data sheet:

## SIGA-Primur® Roll



**Updated on:** 13.05.2013

**Distributor:** SIGA

**Type of application:** durably airtight and windtight joints to plastered masonry and other mineral substrates

**Instructions for application:** see manual

**Construction:** high-performance adhesive compound, permanently strong adhesion and elasticity

**Packaging unit:** 10 rolls / box

### Characteristics:

		Standards	Units	Values
<b>Dimensions</b>	Length Width / thickness		m m	8 0.012 / 0.004
<b>Temperature resistance</b>			°C	- 40 °C to + 100 °C
<b>Processing temperature</b>			°C	from - 10 °C
<b>Diffusion-equivalent air layer thickness <math>s_d</math> (for 4 mm bead thickness)</b>		EN 1931	m	4
<b>airtightness: joint permeability coefficient linear reference air permeability</b>	a-value Q <sub>1000</sub> -value	EN 12114	m <sup>3</sup> /(hmdaPA <sup>2</sup> /3) m <sup>3</sup> /(mh)	< 0.1 ≤ 0.25
<b>Ageing resistance</b>		high permanent adhesive strength, non-drying and non-embrittling since without caoutchouc, resin or solvent, can reliably and durably absorb structural movements		
<b>Suitability for storage</b>		unlimited		