

Product data sheet:

SIGA-Wigluv®



Updated on: 13.05.2013

Distributor: SIGA

Type of application: durably rainproof and windtight joints on facades and inclined roofs

Instructions for application: see manual

Construction: diffusion-open special PO film, elastic, impermeable to water, UV-stable, can be exposed to the atmosphere for 12 months, with SIGA high-performance adhesive

Packaging unit:

Wigluv 60	10 rolls/box
Wigluv 100	6 rolls/box
Wigluv 150	4 rolls/box
Wigluv 20/40	10 rolls/box

Characteristics:

		Standards	Units	Values
Dimensions	Length / width	Wigluv 60	m	40 / 0.06
	Length / width	Wigluv 100	m	25 / 0.10
	Length / width	Wigluv 150	m	25 / 0.15
	Length / width	Wigluv 20/40	m	25 / 0.06
Temperature resistance			°C	- 40 °C to + 100 °C
Processing temperature			°C	from - 10 °C
Atmospheric exposure				max. 12 months
Diffusion-equivalent air layer thickness s_d		EN 1931	m	< 2
Driving-rain-proof	$P_{max.}$	EN 1027 EN 12208	Pa Class	600 9A
Ageing resistance		high permanent adhesive strength, non-drying and non-embrittling since without caoutchouc, resin or solvent, can reliably and durably absorb structural movements		
Suitability for storage		unlimited		